

### TECHNICAL DATA

#### Features

- Measures air velocity (m/s, ft/min, km/h and mph), air temperature and humidity
- Easy to operate, designed for one hand operation
- Integrated display provides flexibility for use without mobile device
- Magnetic backing allows instrument to be mounted to metallic surfaces
- Data Hold function
- Low battery indicator and auto shut off
- Tripod mount for long-term monitoring

#### When used with REED Smart Series App:

- Calculates air volume
- Real-time data logger
- User selectable sampling rate from 1 to 120 seconds
- Bluetooth® 5.0 provides connectivity to instruments up to 246' (75m) away
- Connect, measure and datalog up to 6 instruments, simultaneously
- Easy setup with automatic app integration for compatible REED Smart Series instruments
- Export data via Excel or PDF and create custom reports that can be emailed from mobile device
- Includes 4 x AAA batteries and protective cap

#### Specifications

##### Air Velocity (Anemometer)

Measuring Range:	fpm: 118 to 4921 m/s: 0.6 to 25 km/h: 2.1 to 90 mph: 1.3 to 55.9
Accuracy:	fpm: $\pm(40\text{fpm} + 3.5\%)$ m/s: $\pm(0.2\text{m/s} + 3.5\%)$ km/h: $\pm(0.8\text{km/h} + 3.5\%)$ mph: $\pm(0.5\text{mph} + 3.5\%)$
Resolution:	fpm: 1 m/s: 0.1 km/h: 0.1 mph: 0.1



Continued...

### TECHNICAL DATA

<b>Temperature</b>	
Measuring Range:	-4 to 140°F (-20 to 60°C)
Accuracy:	-4 to 32°F (-20 to 0°C): ±1.6°F (0.8°C) 32 to 140°F (0 to 60°C): ±1°F (0.5°C)
Resolution:	0.1°F/°C
<b>Humidity</b>	
Measuring Range:	0 to 100% RH
Accuracy:	20 to 80% RH: ±3.5% rdg. 0 to 20% & 80 to 100% RH: ±5% rdg.
Resolution:	0.1% RH
<b>General Specifications</b>	
Display:	Multi-Line Enhanced Black Twisted Nematic (EBTN) LCD
Display Size:	1.3" (34mm)
Backlit Display:	Yes
Data Hold:	Yes
Datalogging Capabilities:	Yes (with Smart Series App)
Real-Time Clock and Date Stamp:	Yes (with Smart Series App)
Customizable Sampling Rate:	Yes
Overrange Indicator:	Yes
Auto Shut-off:	Yes (adjustable)
Tripod Mountable:	Yes
Magnetic Backing:	Yes
Low Battery Indicator:	Yes
Power Supply:	4 x AAA Batteries
Battery Life:	Approx. 50 hours (sampling time dependent)
Connectivity:	Bluetooth® 5.0
Bluetooth® Range:	Up to 246' (75m)
Max # of Connected Devices:	6
Software:	REED Smart Series App (iOS and Android)
App Supported Languages:	English, French
Product Certifications:	CE, UKCA, FCC, IC ID
Maximum Operating Altitude:	6561' (2000m)
Operating Temperature:	-4 to 122°F (-20 to 50°C)
Storage Temperature:	-4 to 140°F (-20 to 60°C)
Operating Humidity Range:	10 to 90%
Storage Humidity Range:	10 to 90%
Dimensions:	6.9 x 1.5 x 1" (175 x 38 x 25mm)
Weight:	3.8oz (108g)

Model	Description
R1600	Vane Anemometer
R1600-NIST	Vane Anemometer & NIST
CA-52A	Small Soft Carrying Case
R8888	Medium Hard Carrying Case
R1500	Tripod